

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

CEMENTEK

Technical Specifications

Vehicle Type	Solvent Borne Pure Acrylic
Solvent	High Aromatic White Spirits
Enviro Rating	Flammable 3
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	10 - 15m ² per litre
Apply with	Brush, Roller or spray
Drying time	2 hours @ 25°C (before over coating and foot traffic) 7 days or less (Hard Cure)
Wash ability	Good
Elongation	N/A
Pigment	Non Pigmented
Solids Volume	± 14%
Flexibility	Good
Colour	Transparent
Finish	Semi-gloss
Storage	Cool, dry place. Keep out of reach of children)
Over coating	Over coat with good quality Acrylic Paint)
Packaging	1L, 5L and 20L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Excellent
Resistance to Solvents	Good
Impact Resistance	Very Good
Active Ingredient	Pure Acrylic
Additional Amount	N/A
Caution	Flammable (see Material Safety Data Sheet)
Catalyst Ratio	N/A
Recommended Dry Film	10 microns per coat (2 coats min)
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Very Good
Appearance	Water clear